

Eckel® 20 Standard

Casing Tong 7 - 20 in.

Maximum Torque 42,000 ft-lbs (56944 Nm)



For casing up to 20 inches, here's a tong that combines surprising speed with an ability to handle smaller sizes economically (as small as 7 inches). It reaches peak efficiency at just 38 horse power input, thus requiring no "souped-up" power unit.

Features

- Maximum Torque: 42,000 ft-lbs (56944 Nm)
- Two Speed Gear Train
- Self Aligning Throat
- Drop-in Style Bracket/Mount Shaft Encoder
- Chain Bridle or Solid Hanger
- Wrap-Around Dies or Rig Dies: Steel Fine Tooth / Coarse Tooth

Options

- Wedge Drive Tri-Grip® Backup (Compression or Tension)
- RPM Control
- Torque Turn Control System
- In-line Electronic Dump Valve
- Open/Close Center Convertible Control Valve
- Door Interlock
- Lift Cylinder
- Spring Hanger



TONG SPECIFICATIONS

Capacity	7 - 20 in. (177.8 - 508.0 mm)
Dimensions	43.5 x 75.5 in. (1104.9 x 1917.7 mm)
Weight ^[1]	3,100 lb. (1406.1 kg)
Maximum Torque @ 2,500 psi (172 bar)	
High	8,000 ft-lb (10486 Nm)
Low	42,000 ft-lb (56944 Nm)
Maximum RPM @ 65 GPM (246 LPM)	
High	54 rpm
Low	8 rpm
Handle Length	50 in. (1270 mm)
Certifications	DNV Available

BACKUP SPECIFICATIONS

Backup Type	Wedge Drive Tri-Grip Backup
Capacity	7 - 21 in. (177.8 - 533.4 mm)
Dimensions ^[2]	58 x 78.5 in. (1473.2 x 1993.9 mm)
Weight ^{[1] [2]}	6,100 lb. (2767 kg)
Load Cell Type	Compression or Tension
Handle Length ^[2]	50 in. (1270.0 mm)

^[1] Weight Approximate, ^[2] Tong and Backup

RELIABLE. SAFE. EFFICIENT. TRUSTED.

sales@eckel.com | www.eckel.com

21049

© 2021 Eckel. All rights reserved For more information, contact Eckel at sales@eckel.com Specifications are subject to change without notice. Eckel products named herein may be protected by one or more U.S. and/or foreign patents and patent pending applications. Unless noted otherwise, trademarks herein are the property of Eckel Manufacturing Co., Inc. and may be registered in the United States and/or other countries.